



ООО "НПК "СПЕЦБУРМАТЕРИАЛЫ"

Bridging material Polyfiltrol

Manufacturer
АО «NPO «Polycell» (joint stock company, Russia)

TS 2458-048-97457491-2011



Bridging material Polyfiltrol is designed for plugging water channels in highly permeable, fractured and fissured-cavernous reservoirs, eliminating absorption zones and flow channels in cement stone behind the column.

It is used in the oil and gas industry when drilling wells. Bridging material Polyfiltrol is a composition based on organic fibers with various inorganic modifying additives.

Product Characteristics

Appearance	Loose material from gray to brown color
Filtration time, s, not more	300

Application

Bridging material Polyfiltrol is used to prevent well walls collapse and erosion of rocks in the space behind the casing, separation of water-bearing horizon and other horizons for the study, crack bridging, voids, caverns, for water shutoff, lost circulation control.

Packaging

The product is supplied in polypropylene bags with polyethylene inserts of 25 kg each.

Storage

The product is stored in warehouses. It is allowed to store the product under a canopy or on a planned site, protected from mechanical damage, precipitation, soil moisture and away from sources of fire. The warranty period of storage is 12 months from the date of manufacture, if the consumer observes the requirements of transportation and storage.

Hazard Class

Low-risk product. The hazard class is 4.